

<b>Description</b>	2Kg CO2	4.5 Kg CO2
<b>Capacity of Agent</b>	2kg	4.5kg
<b>Extinguishing Agent</b>	CO2	CO2
<b>Certification</b>	BIS	BIS
<b>Standard Reference</b>	IS 15683:2018	IS 15683:2018
<b>Diameter of Body</b>	Approx. 108 mm	Approx. 140 mm
<b>Total Height</b>	Approx. 577mm	Approx. 724 mm
<b>MOC of Shell</b>	37 Mn/34CrMo4	37Mn/34CrMo4
<b>Sheet Thickness</b>	Minimum 4 mm	Minimum 4 mm
<b>Test Pressure (Min)</b>	225 Bar	225 Bar
<b>Anti Corrosive treatment</b>	Powder Coating	Powder Coating
<b>Body Colour</b>	Red as per IS 5	Red as per IS 5
<b>Service Pressure</b>	Approx. 70 Bar	Approx. 70 Bar
<b>Operating Mechanism</b>	Squeeze Grip .	Squeeze Grip
<b>Pressure Indicating Device</b>	Not Applicable	Not Applicable
<b>Hose Pipe</b>	Not Applicable	EPDM Braided Hose Pipe
<b>Flexible Length of Hose Pipe</b>	Not Applicable	Approx. 1.3 Mtr
<b>BRD(Bulk Range Discharge)</b>	> 2 mtr	> 2 mtr
<b>Minimum Discharge Time</b>	8 sec	8 sec
<b>Discharge Percentage</b>	> 90%	> 90%
<b>Fire Rating</b>	21B	34 B
<b>Applicable to Type of Fire</b>	Class B	Class B
<b>Filled Weight range</b>	Approx. 9.00 kg	Approx. 16.50 kg
<b>Range of Temperature</b>	-30°C to +60°C	-30°C to +60°C